



EMI Shielding Enclosures

Patent Pending

Select Fabricators, Inc.

Products for this millennium

Mini- Enclosures

Tabletop Applications
Portable Shielding

Standard Configuration:

- Patent Pending Single or Double wall EMI shielding tent from 15" x 18" x 11.5" to 4' x 4' x 4' (38cm x 46cm x 29cm to 1.12m x 1.12m x 1.12m). Constructed with RoHS compliant, durable, lightweight Silver/Copper/Nickel fabric. This flexible material offers an average of 86 decibels of shielding effectiveness in the range of 20 MHz to 1 GHz, eliminates stress cracking concerns, and coated to provide protection against galvanic corrosion.
- Roll-up design door with hook 'n loop tabs at the top to keep door open
- Floor is constructed of EMI shielding fabric between two layers of heavy duty tarp.
- Quick-to-assemble aluminum frame with bungee cord attachment system.
- Cable I/O Sleeve



Options:

Ventilation

Two RF Shielded Honeycomb Vents and Fan and Stand Unit that mounts to intake vent.



RF Filter/Ground box attaches to cable I/O sleeve. Filters power line. Optional filtering for Ethernet and USB connectors is available. Filter Box with Ethernet shown at right.



Select Fabricators, Inc. Phone: +1-585-393-0650
Website: select-fabricators.com

Fax: +1-585-393-1378
eMail: contactus@select-fabricators.com

© 2009-10 Select Fabricators, Inc. Rev. 11/03/09